



NOTE:
TERMINAL BOX CAN BE MOUNTED
(LEFT OR RIGHT) BY REFITTING FEET
AND LIFTING LUGS 90° IN APPROPRIATE
DIRECTIONS. CABLE ENTRY CAN BE
SUPPLIED IN ANY ONE OF FOUR
POSITIONS AT 90° INTERVALS.







FIRST ANGLE PROJECTION



Produced by Tamels.A. a company of NB

SHEET SIZE A 3

NOTE!
2.5 ENDPLAY WILL BE PROVIDED FOR ENDTHRUST
PROTECTION WHEN CUSTOMERS NOTIFY US OF THEIR
INTENTION TO USE RIGID COUPLINGS AND DRIVEN
MACHINES WITHOUT ENDPLAY.

OUTLINE DIMENSIONS OF STANDARD FOOT/FLANGE MOUNTED METRIC
A.C. MOTOR TO DIN STANDARD 42673 & 42677.
TOTALLY ENCLOSED FAN VENTILATED.
ASYMMETRICAL FEET. FRAME SIZE: WU-DF315S_E 4P

	NAME	DATE	DRG. No. M9314			1
DRAWN	JM	28-03-11		1710	, O 1	r
CHECKED			DRG. REF. Y57GD0004T			
SCALE	1:8		0,04		DATE	