





T1C200LA-2 30KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type T1C200LA-2 30KW 400/690V B3
Brand BUSCK
Item number 03022001tc

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	30	50	53,6	2920
690	30	50	30,8	2920
460	34,5	60	53,6	3504

Duty	S1	Efficiency, load 100%	90,7
Enclosure	IP55	Efficiency, load 75%	91,4
Insulation class	F	Efficiency, load 50%	89,7
Cooling	IC411 (TEFC)	Power fact, load 100%	0,89
Max. ambient temp.	40°C	Painting	Standard
Min. ambient temp.	-20°C	Color	RAL 9005
Max. temp. rise	80 K	Weight kg	218
Max altitude, masl	1000	Sound pressure Lp dB(A)	92
Torque, Nm	98,12	Bearing DE	6312 C3
Starting torque ratio	2	Bearing NDE	6312 C3
Pull up torque ratio	1,4	Balance grade	Normal
Pull out torque ratio	2,3	Inertia kgm ²	0,15138
Starting current ratio	7,5	Cable entries	2xM50, 1xM16



TC 200L B3

BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no