

TM632-4 0,18kW 230/400V B5

Three-phase asynchronous motor in aluminum

Motor type TM632-4 0,18kW 230/400V B5
Brand BUSCK
Item number 03040642UL

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,18	50	1,1	1365
400	0,18	50	0,63	1365
460	0,21	60	0,63	1638

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 1,2
Starting torque ratio 2,8
Pull up torque ratio 2,4
Pull out torque ratio 2,55
Starting current ratio 3,6

Efficiency class IE1
Efficiency, load 100% 64,2
Efficiency, load 75% 62,5
Efficiency, load 50% 55,9
Power fact, load 100% 0,64

Painting Standard
Color RAL 9005
Weight kg 4,3
Sound pressure Lp dB(A) 52
Bearing DE 6201-2Z/C3
Bearing NDE 6201-2Z/C3
Balance grade Normal
Inertia kgm² 0,000338
Cable entries 1xM20

Note UL approved,
Thermocontact

