

MS90L-8 0,55KW 230/400V B3

Three-phase asynchronous motor in aluminum

Motor type MS90L-8 0,55KW 230/400V B3
Brand BUSCK
Item number 03080911


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,55	50	3,11	680
400	0,55	50	1,79	680
460	0,63	60	1,79	816

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Efficiency class IE1
Efficiency, load 100% 69,0
Efficiency, load 75% 69,9
Efficiency, load 50% 65,8
Power fact, load 100% 0,64

Torque, Nm 7,72
Starting torque ratio 1,6
Pull up torque ratio 1,6
Pull out torque ratio 1,95
Starting current ratio 3,3

Painting Standard
Color RAL 9005
Weight kg 15,3
Sound pressure Lp dB(A) 56
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,004067
Cable entries 1xM20



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no