

MS112M-8 1,5KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type MS112M-8 1,5KW 230/400V B14
 Brand BUSCK
 Item number 03081123

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,5	50	6,92	700
400	1,5	50	3,98	700
460	1,73	60	3,98	840

Duty S1
 Enclosure IP55
 Insulation class F
 Cooling IC411 (TEFC)
 Max. ambient temp. 40°C
 Min. ambient temp. -20°C
 Max. temp. rise 80 K
 Max altitude, masl 1000

Torque, Nm 20,5
 Starting torque ratio 2,2
 Pull up torque ratio 2,1
 Pull out torque ratio 2,5
 Starting current ratio 4,5

Efficiency class IE1
 Efficiency, load 100% 78,3
 Efficiency, load 75% 78,9
 Efficiency, load 50% 76,4
 Power fact, load 100% 0,69

Painting Standard
 Color RAL 9005
 Weight kg 25,5
 Sound pressure Lp dB(A) 61
 Bearing DE 6306-2Z/C3
 Bearing NDE 6206-2Z/C3
 Balance grade Normal
 Inertia kgm² 0,013491
 Cable entries 2xM25

