


Y2-355MB-2 250KW 230/400V B3

Three-phase asynchronous motor in cast iron

Motor type Y2-355MB-2 250KW 230/400V B3
 Brand BUSCK
 Item number 03A23561

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	250	50	715,8	2980
400	250	50	411,6	2980
460	287,5	60	411,6	3576

Duty	S1	Efficiency, load 100%	95,3
Enclosure	IP55	Power fact, load 100%	0,92
Insulation class	F	Painting	Standard
Cooling	IC411 (TEFC)	Color	RAL 9005
Max. ambient temp.	40°C	Weight kg	1760
Min. ambient temp.	-20°C	Sound pressure Lp dB(A)	103
Max. temp. rise	80 K	Balance grade	Normal
Max altitude, masl	1000		
Starting current ratio	7,1		



TYPE	D	E	F	G	DH	ED	L	
Y2-355M/L-2P	Ø75	140	20-Ø043	68	M20x42	110	1500	
Y2-355M/L-4/6/8P	Ø95	170	25-Ø052	86	M24x50	140	1530	short shaft
Y2-355M/L-4/6/8P	Ø100	210	28-Ø052	90	M24x50	160	1570	Long shaft

BUSCK
 www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
 info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
 info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
 info@busck.no