


Y2-355LA-2 280KW 230/400V B3

Three-phase asynchronous motor in cast iron

Motor type Y2-355LA-2 280KW 230/400V B3
Brand BUSCK
Item number 03A23571

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	280	50		
400	280	50		
460	322	60		

Duty	S1	Painting	Standard
Enclosure	IP55	Color	RAL 9005
Insulation class	F	Weight kg	1850
Cooling	IC411 (TEFC)	Balance grade	Normal
Max. ambient temp.	40°C		
Min. ambient temp.	-20°C		
Max. temp. rise	80 K		
Max altitude, masl	1000		



TYPE	D	E	F	G	DH	ED	L	
Y2-355M/L-2P	Ø75	140	20- $\frac{1}{10}$ 43	68	M20x42	110	1500	
Y2-355M/L-4/6/8P	Ø95	170	25- $\frac{1}{10}$ 52	86	M24x50	140	1530	short shaft
Y2-355M/L-4/6/8P	Ø100	210	28- $\frac{1}{10}$ 52	90	M24x50	160	1570	long shaft

BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no