




T1C200L-4 30KW 230/400V B35

Three-phase asynchronous motor in cast iron

Motor type T1C200L-4 30KW 230/400V B35
 Brand BUSCK
 Item number 03A42004tc

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	30	50	93,3	1460
400	30	50	53,6	1460
460	34,5	60	53,6	1752

Duty	S1	Efficiency, load 100%	90,7
Enclosure	IP55	Efficiency, load 75%	92,3
Insulation class	F	Efficiency, load 50%	91,6
Cooling	IC411 (TEFC)	Power fact, load 100%	0,89
Max. ambient temp.	40°C	Painting	Standard
Min. ambient temp.	-20°C	Color	RAL 9005
Max. temp. rise	80 K	Weight kg	216,5
Max altitude, masl	1000	Sound pressure Lp dB(A)	79
Torque, Nm	196,23	Bearing DE	6312 C3
Starting torque ratio	2,2	Bearing NDE	6312 C3
Pull up torque ratio	1,6	Balance grade	Normal
Pull out torque ratio	2,6	Inertia kgm ²	0,26594
Starting current ratio	8	Cable entries	2xM50, 1xM16



TC 200L B35

BUSCK
www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
info@busck.no