

MS132MA-6 4KW 230/400V B3

Three-phase asynchronous motor in aluminum

Motor type MS132MA-6 4KW 230/400V B3
Brand BUSCK
Item number 03A61331


Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	4	50	16,4	960
400	4	50	9,44	960
460	4,6	60	9,44	1152

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 39,79
Starting torque ratio 2
Pull up torque ratio 1,3
Pull out torque ratio 2
Starting current ratio 6,5

Efficiency class EFF2
Efficiency, load 100% 80,5
Power fact, load 100% 0,76

Painting Standard
Color RAL 9005
Weight kg 47,6
Sound pressure Lp dB(A) 68
Bearing DE 6308-2Z/C3
Bearing NDE 6208-2Z/C3
Balance grade Normal
Inertia kgm² 0,0351
Cable entries 2xM25



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no