



**SIMOTICS GP - 90 L - IM B14 - 6p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U                                                   | Δ / Y | f    | P       | P    | I    | n       | M    | η <sup>3)</sup> |                                                  |                        | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------------------------------------------|-------|------|---------|------|------|---------|------|-----------------|--------------------------------------------------|------------------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                 |       | [Hz] | [kW]    | [hp] | [A]  | [1/min] | [Nm] | 4/4             | 3/4                                              | 2/4                    | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| DOL duty (S1) - 155(F) to 130(B)                    |       |      |         |      |      |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
| 230                                                 | Δ     | 50   | 1.10    | -/-  | 5.20 | 950     | 11.1 | 81.0            | 81.4                                             | 79.3                   | 0.66               | 0.57 | 0.44 | 5.0                            | 2.8                            | 3.0                            | IE3   |
| 400                                                 | Y     | 50   | 1.10    | -/-  | 2.95 | 950     | 11.1 | 81.0            | 81.4                                             | 79.3                   | 0.66               | 0.57 | 0.44 | 5.0                            | 2.8                            | 3.0                            | IE3   |
|                                                     |       |      |         |      |      |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |         |      |      |         |      |                 |                                                  |                        |                    |      |      |                                |                                |                                |       |
| IM B14 / IM 3601                                    |       |      | FS 90 L |      |      | IP55    | UKCA | IEC/EN 60034    |                                                  | IEC, DIN, ISO, VDE, EN |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1000 m |       |      |         |      |      |         |      |                 | Locked rotor time (hot / cold) : 31.8 s   40.5 s |                        |                    |      |      |                                |                                |                                |       |

|                                                                                          |                                |                                |                                 |                                         |
|------------------------------------------------------------------------------------------|--------------------------------|--------------------------------|---------------------------------|-----------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                     | 43 / 55 dB(A) <sup>2) 3)</sup> | 46 / 58 dB(A) <sup>2) 3)</sup> | Vibration severity grade        | A                                       |
| Moment of inertia                                                                        | 0.0052 kg m²                   |                                | Thermal class                   | F                                       |
| Bearing DE   NDE                                                                         | 6205 2Z C3                     | 6004 2Z C3                     | Duty type                       | S1                                      |
| <b>bearing lifetime</b>                                                                  |                                |                                | Direction of rotation           | bidirectional                           |
| L <sub>10</sub> mh, F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 40000 h                        | 32000 h                        | Frame material                  | aluminum                                |
| Regreasing device                                                                        | Without                        |                                | Net weight of the motor (IM B3) | 19 kg                                   |
| Grease nipple                                                                            | -/-                            |                                | Coating (paint finish)          | Standard paint finish C2                |
| Type of bearing                                                                          | Preloaded bearing DE           |                                | Color, paint shade              | RAL7030                                 |
| Condensate drainage holes                                                                | Without                        |                                | Motor protection                | (A) without (Standard)                  |
| External earthing terminal                                                               | Without                        |                                | Method of cooling               | IC411 - self ventilated, surface cooled |

|                          |           |                                |              |
|--------------------------|-----------|--------------------------------|--------------|
| Terminal box position    | top       | Max. cross-sectional area      | 1.5 mm²      |
| Material of terminal box | Aluminium | Cable diameter from ... to ... | 9 mm - 17 mm |
| Type of terminal box     | TB1 E00   | Cable entry                    | 1xM25x1,5    |
| Contact screw thread     | M4        | Cable gland                    | 1 plug       |

Notes:

|                                                          |                                           |                                                                  |
|----------------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| $I_{Lr}/I_{Ln}$ = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| $M_r/M_{rn}$ = locked rotor torque / torque nominal      | 2) at rated power / at full load          |                                                                  |
| $M_b/M_{bn}$ = break down torque / nominal torque        |                                           |                                                                  |

|                                                                                    |                             |                               |             |                                                                                                              |                                                                                       |                                |             |
|------------------------------------------------------------------------------------|-----------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|--------------------------------|-------------|
| responsible dep.<br>DI MC LVM                                                      | technical reference         | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                                                                                       | <a href="#">Link documents</a> |             |
|  | document type<br>datasheet  | document status<br>released   |             |                                                                                                              |  |                                |             |
|                                                                                    | title<br>1LE1003-0EC42-2KA4 |                               |             |                                                                                                              |                                                                                       |                                |             |
| © Siemens AG 2023                                                                  |                             |                               |             | rev.<br>943                                                                                                  | creation date<br>2023-06-26                                                           | language<br>en                 | Page<br>1/1 |