

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3162C

SIMOTICS SD - 160 M - IM B5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	7.50	-/-	15.00	985	73.0	89.1	89.7	89.0	0.81	0.76	0.65	7.9	2.3	3.2	IE3
690	Y	50	7.50	-/-	8.70	985	73.0	89.1	89.7	89.0	0.81	0.76	0.65	7.9	2.3	3.2	IE3
IM B5 / IM 3001			FS 160 M				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 13 s 17.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 79 dB(A) ^{2) 3)}	70 / 82 dB(A) ^{2) 3)}	External earthing terminal	Without
Moment of inertia	0.1320 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation 50 60Hz	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	124 kg
Regreasing device	With (standard)		Coating (paint finish)	Special paint finish C3
Grease nipple	M8x1 DIN 71412		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal

M_K/M_N = locked rotor torque / torque nominal

M_B/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010

2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status		
					released		
	title	1LE1603-1DC23-4FB4			document number		
© Siemens AG 2023			rev.	creation date	language	Page	
			943	2023-06-26	en	1/1	