

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3164C

SIMOTICS SD - 160 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	11.00	-/-	22.00	980	107.0	90.3	90.7	89.8	0.80	0.75	0.64	6.8	2.9	2.8	IE3
690	Y	50	11.00	-/-	12.70	980	107.0	90.3	90.7	89.8	0.80	0.75	0.64	6.8	2.9	2.8	IE3
IM B3 / IM 1001			FS 160 L				IP55	UKCA		IEC/EN 60034		IEC, DIN, ISO, VDE, EN					
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 17.9 s 25.4 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	67 / 79 dB(A) ^{2) 3)}	70 / 82 dB(A) ^{2) 3)}	External earthing terminal	Without
Moment of inertia	0.1640 kg m ²		Vibration severity grade	A
Bearing DE NDE	6309 Z C3	6309 Z C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad} ¹⁾ for coupling operation	40000 h	32000 h	Direction of rotation	bidirectional
50 60Hz			Frame material	cast iron
Relubrication interval/quantity DE NDE	10 g 10 g	8000 h	Net weight of the motor (IM B3)	138 kg
Lubricants	Unirex N3		Coating (paint finish)	Special paint finish C3
Regreasing device	With (standard)		Color, paint shade	RAL7030
Grease nipple	M8x1 DIN 71412		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	With (standard)			

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J01	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal 1) L10mh according to DIN ISO 281 10/2010 3) Value is valid only for DOL operation with motor design IC411

M_A/M_N = locked rotor torque / torque nominal 2) at rated power / at full load

M_K/M_N = break down torque / nominal torque

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents		
DI MC LVM		DT Configurator						
	document type	datasheet			document status			
					released			
	title	1LE1603-1DC43-4AB4-Z			document number			
© Siemens AG 2023	H01				rev.	creation date	language	Page
					943	2023-06-26	en	1/2

SIMOTICS SD - 160 L - IM B3 - 6p

Special design

H01	Bolted on mounting feet (instead of cast)
-----	---

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1603-1DC43-4AB4-Z						
	H01			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-26	en	2/2