Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1CV3182A **SIMOTICS SD - 180 M - IM B3 - 2p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	22.00	-/-	67.00	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
400	Y	50	22.00	-/-	38.50	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
460	Y	60	24.50	-/-	37.50	3550	66.0	91.7	92.0	91.4	0.89	0.86	0.79	7.7	2.3	3.6	IE3
460	Y	60	22.00	-/-	34.00	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3
IM B3 / IM 1001		FS 180 M		IP55	UKCA		IEC/EN 60034	IEC, DIN, ISO, VDE, EN									

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 20.1 s | 30.7 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	73 / 80 dB(A) 2) 3)	78 / 85 dB(A) 2) 3)	External earthing terminal	With (standard)
Moment of inertia	0.0800 kg m²		Vibration severity grade	A
Bearing DE | NDE	6310 C3	6310 C3	Thermal class	F
bearing lifetime			Duty type	S1
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE | NDE	15 g | 15 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	160 kg
Regreasing device	With regreasing nipple		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 71412 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J61	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
DI MC LVM		DT Configurator			

SIEMENS

document type	document status
datasheet	released
title: **1LE1603-1EA22-2AB4-Z** **H01+L19+R52**	document number

rev.	creation date	language	Page
943	2023-06-26	en	1/2

© Siemens AG 2023

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1CV3182A **SIMOTICS SD - 180 M - IM B3 - 2p**

Special design

H01	Bolted on mounting feet (instead of cast)	R52	Drilled removable entry plate
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A		

Notes:

responsible dep.	technical reference	created by	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
DI MC LVM		DT Configurator			

SIEMENS	document type: datasheet		document status: released		
	title: 1LE1603-1EA22-2AB4-Z		document number:		
© Siemens AG 2023	H01+L19+R52		rev.: 943	creation date: 2023-06-26	language: en / Page: 2/2