

SIMOTICS SD - 180 M - IM B35 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
500	Δ	50	22.00	-/-	31.00	2950	71.0	92.7	93.2	92.9	0.89	0.86	0.79	7.5	2.3	3.5	IE3
575	Δ	60	24.50	-/-	30.00	3550	66.0	91.7	92.0	91.4	0.89	0.86	0.79	7.7	2.3	3.6	IE3
575	Δ	60	22.00	-/-	27.00	3560	59.0	91.7	91.8	90.9	0.89	0.89	0.80	9.0	2.5	3.9	IE3
IM B35 / IM 2001			FS 180 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 20.1 s 30.7 s								

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 80 dB(A) ^{2) 3)}	78 / 85 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	0.0800 kg m ²		Vibration severity grade	A
Bearing DE NDE	6310 C3	6310 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	15 g 15 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	160 kg
Regreasing device	With regreasing nipple		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 71412 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing NDE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Condensate drainage holes	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J61	Cable entry	2xM40x1,5-1xM16x1,5
Contact screw thread	M5	Cable gland	3 plugs

Notes:

I_{Lr}/I_{Ln} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_{rn} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{bn} = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE1603-1EA24-0JB4-Z						
	H01+L19+R52			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-27	en	1/2

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV3182A

SIMOTICS SD - 180 M - IM B35 - 2p

Special design

H01	Bolted on mounting feet (instead of cast)	R52	Drilled removable entry plate
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1603-1EA24-0JB4-Z			document number			
© Siemens AG 2023	H01+L19+R52			rev. 943	creation date 2023-06-27		