Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1CV3205C **SIMOTICS SD - 200 L - IM B3 - 6p**

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U [V]	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	η 3) 4/4	η 3) 3/4	η 3) 2/4	cosφ 3) 4/4	cosφ 3) 3/4	cosφ 3) 2/4	I_A/I_N I_I/I_N	M_A/M_N T_I/T_N	M_K/M_N T_B/T_N	IE-CL
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	22.00	-/-	76.00	978	215.0	92.2	92.8	92.3	0.79	0.74	0.64	5.6	2.5	2.6	IE3
400	Y	50	22.00	-/-	43.50	978	215.0	92.2	92.8	92.3	0.79	0.74	0.64	5.6	2.5	2.6	IE3

IM B3 / IM 1001		FS 200 L		IP55	UKCA	IEC/EN 60034	IEC, DIN, ISO, VDE, EN		

Environmental conditions : -20 °C - +40 °C / 1000 m

Locked rotor time (hot / cold) : 46.6 s | 69.1 s

Mechanical data

Sound level (SPL / SWL) at 50Hz|60Hz	63 / 76 dB(A) 2) 3)	63 / 70 dB(A) 2) 3)	
Moment of inertia	0.3200 kg m²		
Bearing DE | NDE	6312 C3	6312 C3	
bearing lifetime			
L_{10mh} $F_{Rad\ min}$ for coupling operation 50|60Hz 1)	40000 h	32000 h	
Relubrication interval/quantity DE | NDE	20 g | 20 g 8000 h		
Lubricants	Unirex N3		
Regreasing device	With regreasing nipple		
Grease nipple	M10x1 DIN 71412 A		
Type of bearing	Locating bearing NDE		
Condensate drainage holes	With (standard)		

External earthing terminal	With (standard)
Vibration severity grade	A
Thermal class	F
Duty type	S1
Direction of rotation	bidirectional
Frame material	cast iron
Net weight of the motor (IM B3)	230 kg
Coating (paint finish)	Special paint finish C3
Color, paint shade	RAL7030
Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Max. cross-sectional area	25 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	27 mm - 35 mm
Type of terminal box	TB1 L61	Cable entry	2xM50x1,5-2xM20x1,5
Contact screw thread	M6	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_A/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load
3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents
DI MC LVM		DT Configurator			

SIEMENS

document type	document status
datasheet	released
title: **1LE1603-2AC52-2AB4-Z** **H01+L19+R52**	document number

rev.	creation date	language	Page
943	2023-06-27	en	1/2

© Siemens AG 2023

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS

Motor type : 1CV3205C **SIMOTICS SD - 200 L - IM B3 - 6p**

Special design

H01	Bolted on mounting feet (instead of cast)	R52	Drilled removable entry plate
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.*	Link documents	
SIEMENS	document type datasheet			document status released		
	title 1LE1603-2AC52-2AB4-Z H01+L19+R52			document number		
© Siemens AG 2023				rev. 943	creation date 2023-06-27	language en / Page 2/2