

SIMOTICS SD - 280 M - IM B5 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f [Hz]	P [kW]	P [hp]	I [A]	n [1/min]	M [Nm]	$\eta^{(3)}$			$\cos\varphi^{(3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]								4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	90.00	-/-	265.00	2978	290.0	95.8	95.9	95.4	0.89	0.87	0.80	8.4	2.7	3.5	IE4
400	Y	50	90.00	-/-	152.00	2978	290.0	95.8	95.9	95.4	0.89	0.87	0.80	8.4	2.7	3.5	IE4
460	Y	60	101.00	-/-	148.00	3578	270.0	95.4	95.3	94.6	0.90	0.88	0.83	8.7	3.0	3.3	IE4
460	Y	60	90.00	-/-	133.00	3580	240.0	95.4	95.2	94.2	0.89	0.87	0.80	9.5	3.3	3.7	IE4
IM B5 / IM 3001			FS 280 M			IP55	UKCA	IEC/EN 60034		IEC, DIN, ISO, VDE, EN							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 26.3 s 41.9 s								

Sound level (SPL / SWL) at 50Hz 60Hz	73 / 87 dB(A) ^{2) 3)}	81 / 95 dB(A) ^{2) 3)}	External earthing terminal	With (standard)
Moment of inertia	1.0000 kg m²		Vibration severity grade	A
Bearing DE NDE	6315 C3	6315 C3	Thermal class	F
bearing lifetime			Duty type	S1
L _{10mh} F _{Rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Relubrication interval/quantity DE NDE	25 g 25 g 4000 h		Frame material	cast iron
Lubricants	Unirex N3		Net weight of the motor (IM B3)	610 kg
Regreasing device	With regreasing nipple		Coating (paint finish)	Special paint finish C3
Grease nipple	M10x1 DIN 71412 A		Color, paint shade	RAL7030
Type of bearing	Locating bearing DE		Motor protection	(B) 3 PTC thermistors - for tripping (standard) (2 terminals)
Bearing insulation DE / Bearing insulation NDE	Yes (non-drive end)		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	With (standard)			

Terminal box position	top	Max. cross-sectional area	120 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1 N61	Cable entry	2xM63x1,5-2xM20x1,5
Contact screw thread	M10	Cable gland	4 plugs

Notes:

I_{Lr}/I_{Ln} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_{rn} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{bn} = break down torque / nominal torque		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents 	
	document type datasheet			document status released			
	title 1LE1604-2DA22-2FB4-Z			document number			
© Siemens AG 2023	L19+L51+R52			rev. 943	creation date 2023-06-26	language en	Page 1/2

SIMOTICS SD - 280 M - IM B5 - 2p

L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A	R52	Drilled removable entry plate
L51	Bearing insulation NDE		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
SIEMENS	document type datasheet			document status released			
	title 1LE1604-2DA22-2FB4-Z			document number			
© Siemens AG 2023	L19+L51+R52			rev. 943	creation date 2023-06-26	language en	Page 2/2