



**SIMOTICS SD - 315 S - IM B5 - 2p**

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |

|         |
|---------|
| Remarks |
|---------|

## Safe Area

| U                                                   | Δ / Y | f    | P        | P    | I      | n       | M     | η <sup>3)</sup> |                                                  |              | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------------------------------------------|-------|------|----------|------|--------|---------|-------|-----------------|--------------------------------------------------|--------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                 |       | [Hz] | [kW]     | [hp] | [A]    | [1/min] | [Nm]  | 4/4             | 3/4                                              | 2/4          | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| DOL duty (S1) - 155(F) to 130(B)                    |       |      |          |      |        |         |       |                 |                                                  |              |                    |      |      |                                |                                |                                |       |
| 500                                                 | Δ     | 50   | 110.00   | -/-  | 147.00 | 2988    | 350.0 | 96.0            | 95.9                                             | 95.1         | 0.90               | 0.88 | 0.82 | 9.1                            | 2.5                            | 3.7                            | IE4   |
|                                                     |       |      |          |      |        |         |       |                 |                                                  |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                  |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                  |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                  |              |                    |      |      |                                |                                |                                |       |
| IM B5 / IM3001                                      |       |      | FS 315 S |      |        |         | IP55  | UKCA            |                                                  | IEC/EN 60034 |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1000 m |       |      |          |      |        |         |       |                 | Locked rotor time (hot / cold) : 29.7 s   47.1 s |              |                    |      |      |                                |                                |                                |       |

|                                                                                        |                                            |                                |                                |                                                |           |
|----------------------------------------------------------------------------------------|--------------------------------------------|--------------------------------|--------------------------------|------------------------------------------------|-----------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                   | 72 / 86 dB(A) <sup>2) 3)</sup>             | 77 / 91 dB(A) <sup>2) 3)</sup> | External earthing terminal     | (Standard) Yes                                 |           |
| Moment of inertia                                                                      | 1.8400 kg m²                               |                                | Vibration severity grade       | Grade A                                        |           |
| Bearing DE   NDE                                                                       | 6316 C3                                    | 6316 C3                        | Thermal class                  | F                                              |           |
| permissible lateral force on (N)<br>(N)                                                | X <sub>0</sub> :<br>5800                   | X <sub>0.5</sub> :<br>5500     | X <sub>max</sub> :<br>5200     | Duty type                                      | S1        |
| bearing lifetime                                                                       |                                            |                                | Direction of rotation          | bidirectional                                  |           |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation<br>50 60Hz <sup>1)</sup> | 40000 h                                    | -/-                            |                                | Frame material                                 | cast iron |
| Relubrication interval/quantity DE  <br>NDE                                            | 30 g   30 g<br>3000 h                      |                                | Net weight of the motor        | 957 kg                                         |           |
| Lubricants                                                                             | UNIREX N3                                  |                                | Coating (paint finish)         | Special paint finish C3                        |           |
| Regreasing device                                                                      | with conical grease nipple acc. DIN 71412A |                                | Color, paint shade             | RAL7030                                        |           |
| Grease nipple                                                                          | M10x1 DIN 71412 A                          |                                | Motor protection               | 3 PTC thermistors - for tripping (2 terminals) |           |
| Type of bearing                                                                        | Locating bearing DE                        |                                | Method of cooling              | IC411 - self ventilated, surface cooled        |           |
| Bearing insulation DE / Bearing<br>insulation NDE                                      | Yes (Non-drive end)                        |                                | 'SIMOTICS Connect 400' in IP65 | No                                             |           |
| Condensate drainage holes                                                              | (Standard) Yes                             |                                |                                |                                                |           |

|                          |                |                                |                       |
|--------------------------|----------------|--------------------------------|-----------------------|
| Terminal box position    | box at the top | Max. cross-sectional area      | 240 mm²               |
| Material of terminal box | cast iron      | Cable diameter from ... to ... | 34 mm - 45 mm         |
| Type of terminal box     | TB1Q61         | Cable entry                    | 2xM63x1,5 - 2xM20x1,5 |
| Contact screw thread     | 6xM12          | Cable gland                    | 4 plugs               |

## Notes:

|                                                    |                                           |                                                                  |
|----------------------------------------------------|-------------------------------------------|------------------------------------------------------------------|
| $I_r/I_n$ = locked rotor current / current nominal | 1) L10mh according to DIN ISO 281 10/2010 | 3) Value is valid only for DOL operation with motor design IC411 |
| $M_r/M_n$ = locked rotor torque / torque nominal   | 2) at rated power / at full load          |                                                                  |
| $M_b/M_n$ = break down torque / nominal torque     |                                           |                                                                  |

|                                                                                    |                         |                 |             |                                                                                                              |               |                                                                                       |      |
|------------------------------------------------------------------------------------|-------------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------|------|
| responsible dep.                                                                   | technical reference     | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |               | <a href="#">Link documents</a>                                                        |      |
| DI MC LVM                                                                          |                         | DT Configurator |             |                                                                                                              |               |  |      |
|  | document type           |                 |             | document status                                                                                              |               |  |      |
|                                                                                    | datasheet               |                 |             | released                                                                                                     |               |                                                                                       |      |
|                                                                                    | title                   |                 |             | document number                                                                                              |               |                                                                                       |      |
|                                                                                    | 1LE5504-3AA04-0FB4-Z    |                 |             |                                                                                                              |               |                                                                                       |      |
|                                                                                    | F74+L19+L51+M11+R52+S02 |                 |             | rev.                                                                                                         | creation date | language                                                                              | Page |
| © Siemens AG 2023                                                                  |                         |                 |             | 943                                                                                                          | 2023-06-26    | en                                                                                    | 1/2  |

**SIMOTICS SD - 315 S - IM B5 - 2p**

|     |                                                                   |     |                               |
|-----|-------------------------------------------------------------------|-----|-------------------------------|
| F74 | Sheet steel fan cowl                                              | M11 | Stainless steel rating plate  |
| L19 | Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A | R52 | Drilled removable entry plate |
| L51 | Bearing insulation NDE                                            | S02 | Special paint finish C3       |

Notes:

|                                                                                    |                         |                 |             |                                                                                                              |               |                                                                                       |      |
|------------------------------------------------------------------------------------|-------------------------|-----------------|-------------|--------------------------------------------------------------------------------------------------------------|---------------|---------------------------------------------------------------------------------------|------|
| responsible dep.                                                                   | technical reference     | created by      | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |               | <a href="#">Link documents</a>                                                        |      |
| DI MC LVM                                                                          |                         | DT Configurator |             |                                                                                                              |               |  |      |
|  | document type           |                 |             | document status                                                                                              |               |  |      |
|                                                                                    | datasheet               |                 |             | released                                                                                                     |               |                                                                                       |      |
|                                                                                    | title                   |                 |             | document number                                                                                              |               |                                                                                       |      |
|                                                                                    | 1LE5504-3AA04-0FB4-Z    |                 |             |                                                                                                              |               |                                                                                       |      |
|                                                                                    | F74+L19+L51+M11+R52+S02 |                 |             | rev.                                                                                                         | creation date | language                                                                              | Page |
| © Siemens AG 2023                                                                  |                         |                 |             | 943                                                                                                          | 2023-06-26    | en                                                                                    | 2/2  |