

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4314A

SIMOTICS SD - 315 L - IM B3 - 2p

|                  |                 |           |
|------------------|-----------------|-----------|
| Client order no. | Item-No.        | Offer no. |
| Order no.        | Consignment no. | Project   |
| Remarks          |                 |           |

Electrical data

Safe Area

| U                                                   | Δ / Y | f    | P        | P    | I      | n       | M     | η <sup>3)</sup> |                                                |              | cosφ <sup>3)</sup> |      |      | I <sub>A</sub> /I <sub>N</sub> | M <sub>A</sub> /M <sub>N</sub> | M <sub>K</sub> /M <sub>N</sub> | IE-CL |
|-----------------------------------------------------|-------|------|----------|------|--------|---------|-------|-----------------|------------------------------------------------|--------------|--------------------|------|------|--------------------------------|--------------------------------|--------------------------------|-------|
| [V]                                                 |       | [Hz] | [kW]     | [hp] | [A]    | [1/min] | [Nm]  | 4/4             | 3/4                                            | 2/4          | 4/4                | 3/4  | 2/4  | I <sub>I</sub> /I <sub>N</sub> | T <sub>I</sub> /T <sub>N</sub> | T <sub>B</sub> /T <sub>N</sub> |       |
| DOL duty (S1) - 155(F) to 130(B)                    |       |      |          |      |        |         |       |                 |                                                |              |                    |      |      |                                |                                |                                |       |
| 500                                                 | Δ     | 50   | 160.00   | -/-  | 215.00 | 2986    | 510.0 | 96.3            | 96.3                                           | 95.8         | 0.90               | 0.88 | 0.82 | 9.6                            | 2.5                            | 3.9                            | IE4   |
|                                                     |       |      |          |      |        |         |       |                 |                                                |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                |              |                    |      |      |                                |                                |                                |       |
|                                                     |       |      |          |      |        |         |       |                 |                                                |              |                    |      |      |                                |                                |                                |       |
| IM B3 / IM1001                                      |       |      | FS 315 L |      |        |         | IP55  | UKCA            |                                                | IEC/EN 60034 |                    |      |      |                                |                                |                                |       |
| Environmental conditions : -20 °C - +40 °C / 1000 m |       |      |          |      |        |         |       |                 | Locked rotor time (hot / cold) : 21.4 s   36 s |              |                    |      |      |                                |                                |                                |       |

Mechanical data

|                                                                                     |                                            |                                |                                |                                                |
|-------------------------------------------------------------------------------------|--------------------------------------------|--------------------------------|--------------------------------|------------------------------------------------|
| Sound level (SPL / SWL) at 50Hz 60Hz                                                | 75 / 89 dB(A) <sup>2) 3)</sup>             | 79 / 94 dB(A) <sup>2) 3)</sup> | External earthing terminal     | (Standard) Yes                                 |
| Moment of inertia                                                                   | 2.2500 kg m <sup>2</sup>                   |                                | Vibration severity grade       | Grade A                                        |
| Bearing DE   NDE                                                                    | 6316 C3                                    | 6316 C3                        | Thermal class                  | F                                              |
| permissible lateral force on (N)                                                    | X <sub>0</sub> : 5800                      | X <sub>0.5</sub> : 5500        | Duty type                      | S1                                             |
|                                                                                     |                                            | X <sub>max</sub> : 5200        | Direction of rotation          | bidirectional                                  |
| bearing lifetime                                                                    |                                            |                                | Frame material                 | cast iron                                      |
| L <sub>10mh</sub> F <sub>Rad min</sub> for coupling operation 50 60Hz <sup>1)</sup> | 40000 h                                    | -/-                            | Net weight of the motor        | 1050 kg                                        |
| Relubrication interval/quantity DE   NDE                                            | 30 g   30 g                                | 3000 h                         | Coating (paint finish)         | Special paint finish C3                        |
| Lubricants                                                                          | UNIREX N3                                  |                                | Color, paint shade             | RAL7030                                        |
| Regreasing device                                                                   | with conical grease nipple acc. DIN 71412A |                                | Motor protection               | 3 PTC thermistors - for tripping (2 terminals) |
| Grease nipple                                                                       | M10x1 DIN 71412 A                          |                                | Method of cooling              | IC411 - self ventilated, surface cooled        |
| Type of bearing                                                                     | Locating bearing DE                        |                                | 'SIMOTICS Connect 400' in IP65 | No                                             |
| Bearing insulation DE / Bearing insulation NDE                                      | Yes (Non-drive end)                        |                                |                                |                                                |
| Condensate drainage holes                                                           | (Standard) Yes                             |                                |                                |                                                |

Terminal box

|                          |                |                                |                       |
|--------------------------|----------------|--------------------------------|-----------------------|
| Terminal box position    | box at the top | Max. cross-sectional area      | 240 mm <sup>2</sup>   |
| Material of terminal box | cast iron      | Cable diameter from ... to ... | 34 mm - 45 mm         |
| Type of terminal box     | TB1Q61         | Cable entry                    | 2xM63x1,5 - 2xM20x1,5 |
| Contact screw thread     | 6xM12          | Cable gland                    | 4 plugs               |

Notes:

I<sub>A</sub>/I<sub>N</sub> = locked rotor current / current nominal      1) L10mh according to DIN ISO 281 10/2010      3) Value is valid only for DOL operation with motor design IC411

M<sub>A</sub>/M<sub>N</sub> = locked rotor torque / torque nominal      2) at rated power / at full load

M<sub>K</sub>/M<sub>N</sub> = break down torque / nominal torque

|                                                                                    |                         |                      |             |                                                                                                              |                 |                                                                                       |          |      |
|------------------------------------------------------------------------------------|-------------------------|----------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------|---------------------------------------------------------------------------------------|----------|------|
| responsible dep.                                                                   | technical reference     | created by           | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                 | <a href="#">Link documents</a>                                                        |          |      |
| DI MC LVM                                                                          |                         | DT Configurator      |             |                                                                                                              |                 |  |          |      |
|  | document type           | datasheet            |             |                                                                                                              | document status |                                                                                       |          |      |
|                                                                                    |                         |                      |             |                                                                                                              | released        |                                                                                       |          |      |
|                                                                                    | title                   | 1LE5504-3AA44-0AB4-Z |             |                                                                                                              | document number |                                                                                       |          |      |
|                                                                                    |                         |                      |             |                                                                                                              |                 |                                                                                       |          |      |
| © Siemens AG 2023                                                                  | F74+L19+L51+M11+R52+S02 |                      |             |                                                                                                              | rev.            | creation date                                                                         | language | Page |
|                                                                                    |                         |                      |             |                                                                                                              | 943             | 2023-06-26                                                                            | en       | 1/2  |

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4314A

SIMOTICS SD - 315 L - IM B3 - 2p

Special design

|     |                                                                   |     |                               |
|-----|-------------------------------------------------------------------|-----|-------------------------------|
| F74 | Sheet steel fan cowl                                              | M11 | Stainless steel rating plate  |
| L19 | Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A | R52 | Drilled removable entry plate |
| L51 | Bearing insulation NDE                                            | S02 | Special paint finish C3       |

Notes:

|                               |                               |                               |             |                                                                                                              |                             |                                                                                       |             |
|-------------------------------|-------------------------------|-------------------------------|-------------|--------------------------------------------------------------------------------------------------------------|-----------------------------|---------------------------------------------------------------------------------------|-------------|
| responsible dep.<br>DI MC LVM | technical reference           | created by<br>DT Configurator | approved by | Technical data are subject to change! There may be discrepancies between calculated and rating plate values. |                             | <a href="#">Link documents</a>                                                        |             |
| SIEMENS                       | document type<br>datasheet    |                               |             | document status<br>released                                                                                  |                             |  |             |
|                               | title<br>1LE5504-3AA44-0AB4-Z |                               |             | document number                                                                                              |                             |                                                                                       |             |
| © Siemens AG 2023             | F74+L19+L51+M11+R52+S02       |                               |             | rev.<br>943                                                                                                  | creation date<br>2023-06-26 | language<br>en                                                                        | Page<br>2/2 |