

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4315A

SIMOTICS SD - 315 L - IM B35 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	200.00	-/-	330.00	2986	640.0	96.5	96.6	96.2	0.91	0.90	0.85	9.7	2.7	3.7	IE4
690	Y	50	200.00	-/-	191.00	2986	640.0	96.5	96.6	96.2	0.91	0.90	0.85	9.7	2.7	3.7	IE4
460	Δ	60	200.00	-/-	285.00	3588	530.0	96.2	96.0	95.2	0.91	0.89	0.84	11.0	3.1	4.0	IE4
460	Δ	60	225.00	-/-	325.00	3586	600.0	96.2	96.2	95.6	0.91	0.90	0.86	9.7	2.8	3.6	IE4
IM B35 / IM2001			FS 315 L			IP55	UKCA	IEC/EN 60034									
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 16.5 s 29.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	74 / 89 dB(A) ^{2) 3)}	79 / 93 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	2.7500 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6316 C3	6316 C3	Thermal class	F
permissible lateral force on (N)	X ₀ : 5800	X _{0.5} : 5500	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	30 g 30 g	3000 h	Net weight of the motor	1290 kg
Lubricants	UNIREX N3		Coating (paint finish)	Special paint finish C3
Regreasing device	with conical grease nipple acc. DIN 71412A		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes		'SIMOTICS Connect 400' in IP65	No

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	34 mm - 45 mm
Type of terminal box	TB1Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE5504-3AA53-4JB4-Z				
© Siemens AG 2023	F74+L19+M11+R52+S02				rev.
					943
		creation date		language	Page
		2023-06-26		en	1/2



SIMOTICS SD - 315 L - IM B35 - 2p

F74	Sheet steel fan cowl	R52	Drilled removable entry plate
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A	S02	Special paint finish C3
M11	Stainless steel rating plate		

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE5504-3AA53-4JB4-Z			document number			
© Siemens AG 2023	F74+L19+M11+R52+S02			rev. 943	creation date 2023-06-26	language en	Page 2/2