

SIMOTICS SD - 315 L - IM B35 - 2p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
400	Δ	50	250.00	-/-	425.00	2986	800.0	96.5	96.4	95.7	0.88	0.85	0.77	9.3	3.0	4.2	IE4
690	Y	50	250.00	-/-	245.00	2986	800.0	96.5	96.4	95.7	0.88	0.85	0.77	9.3	3.0	4.2	IE4
460	Δ	60	250.00	-/-	370.00	3588	670.0	96.2	95.8	94.8	0.88	0.84	0.76	11.0	4.1	4.6	IE4
460	Δ	60	280.00	-/-	415.00	3586	750.0	96.2	95.9	95.1	0.88	0.85	0.78	9.6	3.7	4.1	IE4
IM B35 / IM2001			FS 315 L			IP55	UKCA	IEC/EN 60034									
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 39.1 s 63.3 s								

Sound level (SPL / SWL) at 50Hz 60Hz	80 / 94 dB(A) ^{2) 3)}	84 / 98 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes	
Moment of inertia	2.8200 kg m²		Vibration severity grade	Grade A	
Bearing DE NDE	6316 C4	6316 C4	Thermal class	F	
permissible lateral force on (N) (N)	X ₀ : 5800	X _{0.5} : 5500	X _{max} : 5200	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional	
L _{10mh} F _{rad,min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron	
Relubrication interval/quantity DE NDE	30 g 30 g 3000 h		Net weight of the motor	1408 kg	
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2	
Regreasing device	with conical grease nipple acc. DIN 71412A		Color, paint shade	RAL7030	
Grease nipple	M10x1 DIN 71412 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)	
Type of bearing	Locating bearing DE		Method of cooling	IC411 - self ventilated, surface cooled	
Bearing insulation DE / Bearing insulation NDE	Yes (Non-drive end)		'SIMOTICS Connect 400' in IP65	No	
Condensate drainage holes	(Standard) Yes				

Terminal box position	box at the angle 45°, socket right	Max. cross-sectional area	240 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	42 mm - 54 mm
Type of terminal box	TB3Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_{lr}/I_{ln} = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_{lr}/M_{ln} = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_{ln} = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AA63-4JB3-Z						
	L19+L51			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-26	en	1/2

SIMOTICS SD - 315 L - IM B35 - 2p

Special design

L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A	L51	Bearing insulation NDE
-----	---	-----	------------------------

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AA63-4JB3-Z						
	L19+L51			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-26	en	2/2