

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4310C

SIMOTICS SD - 315 S - IM B5 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project
Remarks		

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cos φ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
230	Δ	50	75.00	-/-	235.00	992	720.0	95.4	95.6	95.2	0.84	0.79	0.69	8.2	2.7	3.5	IE4
400	Y	50	75.00	-/-	135.00	992	720.0	95.4	95.6	95.2	0.84	0.79	0.69	8.2	2.7	3.5	IE4
460	Y	60	90.00	-/-	139.00	1192	720.0	95.8	96.0	95.7	0.85	0.81	0.72	8.0	2.5	3.3	IE4
IM B5 / IM3001			FS 315 S			IP55	UKCA	IEC/EN 60034									
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 25 s 33.9 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	63 / 77 dB(A) ^{2) 3)}	65 / 79 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	3.1800 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
permissible lateral force on (N) (N)	X ₀ : 10600	X _{0.5} : 9900	Duty type	S1
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Frame material	cast iron
Relubrication interval/quantity DE NDE	40 g 40 g	6000 h	Net weight of the motor	879 kg
Lubricants	UNIREX N3		Coating (paint finish)	Standard paint finish C2
Regreasing device	with conical grease nipple acc. DIN 71412A		Color, paint shade	RAL7030
Grease nipple	M10x1 DIN 71412 A		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Type of bearing	Locating bearing NDE		Method of cooling	IC411 - self ventilated, surface cooled
Condensate drainage holes	(Standard) Yes		'SIMOTICS Connect 400' in IP65	No

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1Q01	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I_A/I_N = locked rotor current / current nominal
M_K/M_N = locked rotor torque / torque nominal
M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type	datasheet			document status		
					released		
	title	1LE5504-3AC02-2FB4-Z			document number		
© Siemens AG 2023	F74+L19+M11		rev.	creation date	language	Page	
			943	2023-06-26	en	1/2	

SIMOTICS SD - 315 S - IM B5 - 6p

--

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet			document status released			
	title 1LE5504-3AC02-2FB4-Z			document number			
© Siemens AG 2023	F74+L19+M11			rev. 943	creation date 2023-06-26	language en	Page 2/2