

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type : 1CV4315C

SIMOTICS SD - 315 L - IM B3 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	η ³⁾			cosφ ³⁾			I _A /I _N	M _A /M _N	M _K /M _N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I _I /I _N	T _I /T _N	T _B /T _N	
DOL duty (S1) - 155(F) to 130(B)																	
500	Δ	50	132.00	-/-	182.00	992	1270.0	96.0	96.3	96.3	0.87	0.83	0.74	8.4	2.8	3.5	IE4
IM B3 / IM1001			FS 315 L				IP55	UKCA		IEC/EN 60034							
Environmental conditions : -20 °C - +40 °C / 1000 m									Locked rotor time (hot / cold) : 22.8 s 33.2 s								

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	64 / 79 dB(A) ^{2) 3)}	66 / 81 dB(A) ^{2) 3)}	External earthing terminal	(Standard) Yes
Moment of inertia	5.3200 kg m ²		Vibration severity grade	Grade A
Bearing DE NDE	6319 C3	6319 C3	Thermal class	F
permissible lateral force on (N)	X ₀ : 10600	X _{0.5} : 9900	Duty type	S1
(N)				
bearing lifetime			Direction of rotation	bidirectional
L _{10mh} F _{Rad min} for coupling operation	40000 h	-/-	Frame material	cast iron
50 60Hz ¹⁾			Net weight of the motor	1130 kg
Relubrication interval/quantity DE	40 g 40 g		Coating (paint finish)	Special paint finish C3
NDE	6000 h		Color, paint shade	RAL7030
Lubricants	UNIREX N3		Motor protection	3 PTC thermistors - for tripping (2 terminals)
Regreasing device	with conical grease nipple acc. DIN 71412A		Method of cooling	IC411 - self ventilated, surface cooled
Grease nipple	M10x1 DIN 71412 A		'SIMOTICS Connect 400' in IP65	No
Type of bearing	Locating bearing NDE			
Condensate drainage holes	(Standard) Yes			

Terminal box

Terminal box position	box at the top	Max. cross-sectional area	240 mm ²
Material of terminal box	cast iron	Cable diameter from ... to ...	38 mm - 45 mm
Type of terminal box	TB1Q61	Cable entry	2xM63x1,5 - 2xM20x1,5
Contact screw thread	6xM12	Cable gland	4 plugs

Notes:

I _A /I _N = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M _A /M _N = locked rotor torque / torque nominal	2) at rated power / at full load	
M _K /M _N = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.	Link documents
DI MC LVM		DT Configurator			
	document type				document status
	datasheet				released
	title				document number
	1LE5504-3AC54-0AB4-Z				
© Siemens AG 2023	F74+L19+M11+R52+S02				rev.
					943
		creation date		language	Page
		2023-06-26		en	1/2



SIMOTICS SD - 315 L - IM B3 - 6p

F74	Sheet steel fan cowl	R52	Drilled removable entry plate
L19	Regreasing device with regreasing nipple M10X1 acc.to DIN 71412-A	S02	Special paint finish C3
M11	Stainless steel rating plate		

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1LE5504-3AC54-0AB4-Z						
	F74+L19+M11+R52+S02			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-26	en	2/2