

SIMOTICS XP - 160 M - IM B34 - 6p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

II 2G Ex db eb IIC T4 Gb

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_A/I_N	T_I/T_N	T_B/T_N	

[illegible]

40	Y	5	0.41		11.1	88	44.1		0.77	Type of converter	Voltage source converter, general.
200	Y	25	3.2		14.3	482	63.4		0.74		
400	Y	50	7		15.1	982	67.7		0.75		
400	Y	95	7		13.9	1865	35.8		0.77		

IM B34 / IM 2101	FS 160 M	IP65	IEC/EN 60034
------------------	----------	------	--------------

Locked rotor time (hot / cold) : 19.9 s | 25.4 s

Sound level (SPL / SWL) at 50Hz 60Hz	59 / 67 dB(A) ^{2) 3)}	75 / 83 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.1360 kg m²		Duty type	S1
Bearing DE NDE	6309 C3	6309 C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Net weight of the motor	196 kg
Regreasing device	Without		Motor weight incl. options	196 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J21	Cable entry	-/-
Contact screw thread	M5		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1553-1DC29-0NB4-Z						
	B32+B43+M4A			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-27	en	1/2

SIMOTICS XP - 160 M - IM B34 - 6p

B32	Design additional for dust Ex tb – zone 21; IP65	M4A	400 VY for 50 Hz
B43	Version for converter operation with operating data on voltage-source DC link converter		

Notes:

responsible dep. DI MC LVM	technical reference	created by DT Configurator	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
	document type datasheet	document status released					
	title 1MB1553-1DC29-0NB4-Z						
© Siemens AG 2023	B32+B43+M4A	rev. 943	creation date 2023-06-27		language en	Page 2/2	