

SIMOTICS XP - 160 M - IM B35 - 4p

Client order no.	Item-No.	Offer no.
Order no.	Consignment no.	Project

Remarks

II 2G Ex db eb IIB T4 Gb

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos \varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_I/I_N	T_I/T_N	T_B/T_N	

400	Δ	50	11.00	-/-	20.50	1475	71.0	91.4	91.8	91.2	0.84	0.79	0.69	7.6	2.6	3.4	IE3
690	Υ	50	11.00	-/-	12.00	1475	71.0	91.4	91.8	91.2	0.84	0.79	0.69	7.6	2.6	3.4	IE3
460	Δ	60	11.00	-/-	18.00	1775	59.0	92.4	92.3	91.1	0.83	0.78	0.67	8.9	3.0	3.8	IE3

40	Δ	5	0.61		14.4	134	43.2		0.80	Type of converter	Voltage source converter, general.
200	Δ	25	4.7		18.5	730	61.8		0.82		
400	Δ	50	10.2		19.5	1475	66		0.83		
400	Δ	100	10.2		17.8	2955	33		0.85		

IM B35 / IM 2001	FS 160 M	IP55	IEC/EN 60034
------------------	----------	------	--------------

Locked rotor time (hot / cold) : 24.3 s | 32.5 s

Sound level (SPL / SWL) at 50Hz 60Hz	69 / 77 dB(A) ^{2) 3)}	69 / 81 dB(A) ^{2) 3)}	Thermal class	F
Moment of inertia	0.0733 kg m²		Duty type	S1
Bearing DE NDE	6309 C3	6309 C3	Direction of rotation	bidirectional
bearing lifetime			Frame material	cast iron
L _{10mh} F _{Rad, min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Net weight of the motor	177 kg
Regreasing device	Without		Motor weight incl. options	177 kg
Grease nipple	-/-		Coating (paint finish)	Standard paint finish C2
Type of bearing	Locating bearing DE		Color, paint shade	RAL7030
Condensate drainage holes	Without		Motor protection	(B) 3 PTC thermistors - for tripping (2 terminals)
External earthing terminal	With (standard)		Method of cooling	IC411 - self ventilated, surface cooled
Vibration severity grade	A			

Terminal box position	top	Max. cross-sectional area	16 mm²
Material of terminal box	cast iron	Cable diameter from ... to ...	19 mm - 28 mm
Type of terminal box	TB1 J21	Cable entry	-/-
Contact screw thread	M5		

I_{lr}/I_n = locked rotor current / current nominal	1) L10mh according to DIN ISO 281 10/2010	3) Value is valid only for DOL operation with motor design IC411
M_r/M_n = locked rotor torque / torque nominal	2) at rated power / at full load	
M_b/M_n = break down torque / nominal torque		

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1563-1DB23-4JB4-Z						
© Siemens AG 2023	B43						
				rev.	creation date	language	Page
				943	2023-06-27	en	1/2

SIMOTICS XP - 160 M - IM B35 - 4p

B43	Version for converter operation with operating data on voltage-source DC link converter
-----	---

B43

Version for converter operation with operating data on voltage-source DC link converter

Notes:

responsible dep.	technical reference	created by	approved by	Technical data are subject to change! There may be discrepancies between calculated and rating plate values.		Link documents	
DI MC LVM		DT Configurator					
	document type			document status			
	datasheet			released			
	title			document number			
	1MB1563-1DB23-4JB4-Z						
	B43			rev.	creation date	language	Page
© Siemens AG 2023				943	2023-06-27	en	2/2