ELK MOTOR SAN. ve TİC. A.Ş.
www.elkmotor.com.tr
+90 (0 282) 726 92 94

DATASHEET

THREE PHASE INDUCTION MOTOR - SQUIRREL CAGE

IE3

Type : 3EL090L6C-PC-A0-000 **Date** : 03.01.2022

Power [kW]	: 1.10	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Y	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 090L
Pole Number	: 6	Weight [kg]	: 17.0
Nominal Speed [rpm]	: 940	Insulation Class	: F [155°C]
Nominal Current [A]	: 2.75	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 11.2	Protection Class	: IP55
Nominal Efficiency [η]	: 81.0	Vibration Severity Grade	: A
Power Factor [cosφ]	: 0.71	Method of Cooling	: IC411
Locked Rotor Current [Ia/In]	: 5.0	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.2	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 2.7	Motor Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 46

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	Cosφ
Δ	230	50	1.10	940	4.76	81.0	0.71
Y	400	50	1.10	940	2.75	81.0	0.71
Y	460	60	1.28	1140	2.71	82.1	0.72

MECHANICAL DATA

Moment of Inertia [kgm^2]	: 0.00428
Bearing DS / NS	: 6205ZZ / 6205ZZ
Frame Material	: Aluminum
Flange Type / Material	: B34 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M20x1.5
Terminal Box Blind Cap	: M16x1.5
Contact Screw Thread	: M4

MECHANICAL DIMENSIONS



FLANGE TYPE	D	N	P	E	T	LA	L	AC	S	M	H	HE	HD	F	GA	DB	C	ØK	B	BB	HA	AA	A	AB
B34	24	95	136.5	50	3	15	325	176	M8	115	90	132	222	8	27	M8	56	10	125	151	4	27	140	167

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.
*ELK Motor has right to change all the data without prior notice.