

Type : 3EL112M4D-PD-B0-000**Date** : 03.01.2022

Power [kW]	: 4.00	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 112M
Pole Number	: 4	Weight [kg]	: 33.9
Nominal Speed [rpm]	: 1460	Insulation Class	: F [155°C]
Nominal Current [A]	: 8.05	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 26.2	Protection Class	: IP55
Nominal Efficiency [η]	: 88.6	Vibration Severity Grade	: A
Power Factor [cosφ]	: 0.81	Method of Cooling	: IC411
Locked Rotor Current [Ia/In]	: 7.4	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.8	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.8	Motor Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 58

ELECTRICAL DATA


Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	cosφ
Δ	400	50	4.00	1460	8.05	88.6	0.81
Y	690	50	4.00	1460	4.65	88.6	0.81
Δ	460	60	4.55	1755	7.78	89.5	0.82

MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.01437
Bearing DS / NS	: 6206ZZ / 6206ZZ
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M25x1.5
Terminal Box Blind Cap	: M25x1.5
Contact Screw Thread	: M5

MECHANICAL DIMENSIONS

Manufactured and tested in accordance with IEC 60034

FR.AG.010 REV. NO: 03 REV TARİHİ : 01.01.2021

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.