

Type : 3EL132S2C-PA-B0-000**Date** : 03.01.2022

Power [kW]	: 7.50	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 132S
Pole Number	: 2	Weight [kg]	: 51.5
Nominal Speed [rpm]	: 2945	Insulation Class	: F [155°C]
Nominal Current [A]	: 13.2	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 24.3	Protection Class	: IP55
Nominal Efficiency [η]	: 90.1	Vibration Severity Grade	: A
Power Factor [$\cos\phi$]	: 0.91	Method of Cooling	: IC411
Locked Rotor Current [I_a/I_n]	: 8.4	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.6	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 4.0	Motor Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 67

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	$\cos\phi$
Δ	400	50	7.50	2945	13.2	90.1	0.91
Y	690	50	7.50	2945	7.62	90.1	0.91
Δ	460	60	8.70	3535	13.2	90.2	0.92

MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.02104
Bearing DS / NS	: 6208ZZ / 6208ZZ
Frame Material	: Aluminum
Flange Type / Material	: B35 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M25x1.5
Terminal Box Blind Cap	: M25x1.5
Contact Screw Thread	: M5

MECHANICAL DIMENSIONS

FLANGE TYPE	D	E	N	P	T	LA	L	AC	S	M	H	HE	HD	F	GA	DB	C	ØK	B	BB	HA	AA	A	AB
B35	38	80	230	300	4	20	495	257	14.5	265	132	181	313	10	41	M12	89	12	140	212	5	34	216	254

Manufactured and tested in accordance with IEC 60034

FR.AG.010 REV. NO: 03 REV TARİHİ : 01.01.2021

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*ELK Motor has right to change all the data without prior notice.