

T4A63A-2 0,18KW 230/400V B35

Three-phase asynchronous motor in aluminum

Motor type T4A63A-2 0,18KW 230/400V B35
Brand BUSCK
Item number 43020634

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,18	50	0,85	2870
400	0,18	50	0,49	2870
460	0,21	60	0,49	3444


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 0,6240
Starting torque ratio 2,6
Pull up torque ratio 2,0
Pull out torque ratio 2,9
Starting current ratio 5,5
This motor has DNV type approval

Efficiency class IE4
Efficiency, load 100% 70,8
Efficiency, load 75% 68,8
Efficiency, load 50% 63,6
Power fact, load 100% 0,75

Painting Standard
Color RAL 9005
Weight kg 3,8
Sound pressure Lp dB(A) 61
Bearing DE 6201 2RZ C3
Bearing NDE 6201 2RZ C3
Balance grade Normal
Inertia kgm² 0,000245
Cable entries 1xM20

Note Termokontakt
IE4



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no