

T4A80B-2 1,1KW 230/400V B34

Three-phase asynchronous motor in aluminum

Motor type T4A80B-2 1,1KW 230/400V B34
Brand BUSCK
Item number 43020815

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	1,1	50	3,95	2910
400	1,1	50	2,27	2910
460	1,27	60	2,27	3492

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Efficiency class IE4
Efficiency, load 100% 85,2
Efficiency, load 75% 85,2
Efficiency, load 50% 83,3
Power fact, load 100% 0,82

Torque, Nm 3,7612
Starting torque ratio 4,0
Pull up torque ratio 2,6
Pull out torque ratio 4,2
Starting current ratio 10,0
This motor has DNV type approval

Painting Standard
Color RAL 9005
Weight kg 12
Sound pressure Lp dB(A) 67
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm² 0,001508
Cable entries 1xM20

Note Termokontakt
IE4

