

T4A90L-2 2,2KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type T4A90L-2 2,2KW 230/400V B14
Brand BUSCK
Item number 43020913

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	2,2	50	7,57	2900
400	2,2	50	4,35	2900
460	2,53	60	4,35	3480

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,5483
Starting torque ratio 4,0
Pull up torque ratio 3,0
Pull out torque ratio 4,2
Starting current ratio 10,5
This motor has DNV type approval

Efficiency class IE4
Efficiency, load 100% 88,0
Efficiency, load 75% 88,2
Efficiency, load 50% 86,9
Power fact, load 100% 0,83

Painting Standard
Color RAL 9005
Weight kg 18,5
Sound pressure Lp dB(A) 72
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,003086
Cable entries 1xM20

Note Termokontakt
IE4

