

T4A132SA-2 5,5KW 400/690V B3


Three-phase asynchronous motor in aluminum

Motor type T4A132SA-2 5,5KW 400/690V B3
Brand BUSCK
Item number 43021321

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	9,93	2940
690	5,5	50	5,71	2940
460	6,33	60	9,93	3528

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	90,9
Insulation class	F	Efficiency, load 75%	90,9
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,5
Max. ambient temp.	45°C	Power fact, load 100%	0,90
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	49
Torque, Nm	18,614	Sound pressure Lp dB(A)	80
Starting torque ratio	3,4	Bearing DE	6308-2Z/C3
Pull up torque ratio	4,0	Bearing NDE	6208-2Z/C3
Pull out torque ratio	2,3	Balance grade	Normal
Starting current ratio	10,5	Inertia kgm ²	0,017735
This motor has DNV type approval		Cable entries	2xM25, 1xM16

Note Termokontakt
IE4



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no