

T4CR160MA-2 11KW 400/690V B5



Three-phase asynchronous motor in cast iron

Motor type T4CR160MA-2 11KW 400/690V B5
Brand BUSCK
Item number 43021602T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	11	50	19,3	2960
690	11	50	11,08	2960
460	12,65	60	19,3	3552

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	92,6
Insulation class	F	Efficiency, load 75%	92,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	92,5
Max. ambient temp.	40°C	Power fact, load 100%	0,89
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	129
Torque, Nm	35,5	Sound pressure Lp dB(A)	81
Starting torque ratio	2	Bearing DE	6309-2Z/C3
Pull up torque ratio	1,2	Bearing NDE	6309-2Z/C3
Pull out torque ratio	2,3	Balance grade	Normal
Starting current ratio	9,5	Inertia kgm ²	0,069510832733
		Cable entries	2xM32, 1xM16

Note IE4 Förstärkt isolation



TC 160M B5

BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no