

SSWE160MB-2 15KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type SSWE160MB-2 15KW 400/690V B3
Brand BUSCK
Item number 43021611w

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	15	50	26,4	2945
690	15	50	15,2	2945
460	17,25	60	26,4	3534

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	93,3
Insulation class	F	Efficiency, load 75%	93,1
Cooling	IC411 (TEFC)	Efficiency, load 50%	92,0
Max. ambient temp.	40°C	Power fact, load 100%	0,88
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	124
Torque, Nm	49	Sound pressure Lp dB(A)	69
Starting torque ratio	2,2	Bearing DE	6209-2Z/C3
Starting current ratio	8,2	Bearing NDE	6209-2Z/C3
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	0,068
Note	IE4, Kopplingslåda med kabelanslutning Färg svart		

