

SSWE180M-2 22KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type SSWE180M-2 22KW 400/690V B3
Brand BUSCK
Item number 43021801

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	38,4	2955
690	22	50	22,1	2955
460	25,3	60	38,4	3546

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	94
Insulation class	F	Efficiency, load 75%	93,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	92,5
Max. ambient temp.	40°C	Power fact, load 100%	0,88
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	177
Torque, Nm	71	Sound pressure Lp dB(A)	70
Starting torque ratio	2,5	Bearing DE	6211
Starting current ratio	8	Bearing NDE	6211
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	0,173
Note	IE4, Kopplingslåda med 3-2-poler Färg svart		
	Cable entry 1 x M40 + 1 x M16 2 x M40, 1 x M16		

