

T4CR200LA-2 30KW 400/690V B5




Three-phase asynchronous motor in cast iron

Motor type T4CR200LA-2 30KW 400/690V B5
Brand BUSCK
Item number 43022002T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	30	50	51,5	2970
690	30	50	29,6	2970
460	34,5	60	51,5	3564

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	94,5
Insulation class	F	Efficiency, load 75%	94,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,3
Max. ambient temp.	40°C	Power fact, load 100%	0,89
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	278
Torque, Nm	96,5	Sound pressure Lp dB(A)	84
Starting torque ratio	2	Bearing DE	6312 C3
Pull up torque ratio	1,1	Bearing NDE	6312 C3
Pull out torque ratio	2,3	Balance grade	Normal
Starting current ratio	9	Inertia kgm2	0,26694237979
		Cable entries	2xM50, 1xM16

Note IE4 Förstärkt isolation



TC 200L B5

BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no