

T4A80A-4 0,55KW 230/400V B14

Three-phase asynchronous motor in aluminum

Motor type T4A80A-4 0,55KW 230/400V B14
Brand BUSCK
Item number 43040803

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,55	50	2,45	1440
400	0,55	50	1,41	1440
460	0,63	60	1,41	1728

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 3,8003
Starting torque ratio 3,4
Pull up torque ratio 3,0
Pull out torque ratio 3,7
Starting current ratio 6,8
This motor has DNV type approval

Efficiency class IE4
Efficiency, load 100% 83,9
Efficiency, load 75% 83,3
Efficiency, load 50% 80,6
Power fact, load 100% 0,67

Painting Standard
Color RAL 9005
Weight kg 11
Sound pressure Lp dB(A) 57
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm² 0,002047
Cable entries 1xM20

Note Termokontakt
IE4

