

T4A80B-4 0,75KW 230/400V B35

Three-phase asynchronous motor in aluminum

Motor type T4A80B-4 0,75KW 230/400V B35
Brand BUSCK
Item number 43040814

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	0,75	50	3,43	1450
400	0,75	50	1,97	1450
460	0,86	60	1,97	1740

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 5,1466
Starting torque ratio 3,7
Pull up torque ratio 3,1
Pull out torque ratio 4,0
Starting current ratio 7,3
This motor has DNV type approval

Efficiency class IE4
Efficiency, load 100% 85,7
Efficiency, load 75% 85,3
Efficiency, load 50% 82,8
Power fact, load 100% 0,67

Painting Standard
Color RAL 9005
Weight kg 13
Sound pressure Lp dB(A) 58
Bearing DE 6204-2Z/C3
Bearing NDE 6204-2Z/C3
Balance grade Normal
Inertia kgm² 0,002646
Cable entries 1xM20

Note Termokontakt
IE4

