

T4A132S-4 5,5KW 400/690V B35

Three-phase asynchronous motor in aluminum

Motor type T4A132S-4 5,5KW 400/690V B35
Brand BUSCK
Item number 43041324

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	10,9	1470
690	5,5	50	6,27	1470
460	6,33	60	10,9	1764

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	91,9
Insulation class	F	Efficiency, load 75%	92,2
Cooling	IC411 (TEFC)	Efficiency, load 50%	91,5
Max. ambient temp.	45°C	Power fact, load 100%	0,80
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	56
Torque, Nm	37,228	Sound pressure Lp dB(A)	71
Starting torque ratio	3,4	Bearing DE	6308-2Z/C3
Pull up torque ratio	4,1	Bearing NDE	6208-2Z/C3
Pull out torque ratio	2,1	Balance grade	Normal
Starting current ratio	10,0	Inertia kgm ²	0,043597
This motor has DNV type approval		Cable entries	2xM25, 1xM16

Note Termokontakt
IE4

