

T4CR160M-4 11KW 400/690V B35


Single-phase asynchronous motor in aluminum

Motor type T4CR160M-4 11KW 400/690V B35
 Brand BUSCK
 Item number 43041604T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	11	50	20,5	1475
690	11	50	11,79	1475
460	12,65	60	20,5	1770

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	93,3
Insulation class	F	Efficiency, load 75%	93,5
Cooling	IC411 (TEFC)	Efficiency, load 50%	92,8
Max. ambient temp.	45°C	Power fact, load 100%	0,83
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
Torque, Nm	71,25	Weight kg	160
Starting torque ratio	2	Sound pressure Lp dB(A)	73
Pull up torque ratio	1,4	Bearing DE	6309 C3
Pull out torque ratio	2,3	Bearing NDE	6309 C3
Starting current ratio	9,5	Balance grade	Normal
This motor has DNV type approval		Inertia kgm ²	0,1443315633
		Cable entries	2xM32, 1xM16

Note IE4



BUSCK
www.busck.eu

Busck & Co AB
 Gamla Riksvägen 14
 428 32 Göteborg
 Sweden
 556027-1990
info@busck.se

Busck & Co ApS
 Postboks 108
 0900 København C
 Denmark
info@busck.eu

Busck AS
 Skibåsen 35C
 4636 Kristiansand
 Norway
info@busck.no