


SSWE180L-4 22KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type SSWE180L-4 22KW 400/690V B35
Brand BUSCK
Item number 43041814

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	22	50	41,0	1475
690	22	50	23,6	1475
460	25,3	60	41,0	1770

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	94,5
Insulation class	F	Efficiency, load 75%	94,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	93,3
Max. ambient temp.	40°C	Power fact, load 100%	0,83
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	195
Torque, Nm	142	Sound pressure Lp dB(A)	65
Starting torque ratio	2,3	Bearing DE	6311
Starting current ratio	8,5	Bearing NDE	6211
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	0,193
Note	IE4, Kopplingslåda med 3-2-pol + 1 x M16 2xM40, 1xM16		



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no