

SSWE200L-4 30KW 400/690V B35

Three-phase asynchronous motor in cast iron

Motor type SSWE200L-4 30KW 400/690V B35
Brand BUSCK
Item number 43042004

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	30	50	53,7	1480
690	30	50	30,9	1480
460	34,5	60	53,7	1776

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	94,9
Insulation class	F	Efficiency, load 75%	94,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	93,7
Max. ambient temp.	40°C	Power fact, load 100%	0,84
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	250
Torque, Nm	194	Sound pressure Lp dB(A)	68
Starting torque ratio	1,9	Bearing DE	6312
Starting current ratio	7,3	Bearing NDE	6212
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	0,311
Note	IE4, Kopplingslåda med 2 x M16 + 1 x M16	2 x M50, 1 x M16	
	Färg svart		

