

SSWE250M-4 55KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type SSWE250M-4 55KW 400/690V B5
Brand BUSCK
Item number 43042502

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	55	50	97,6	1485
690	55	50	56,1	1485
460	63,25	60	97,6	1782

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	95,7
Insulation class	F	Efficiency, load 75%	95,6
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,8
Max. ambient temp.	40°C	Power fact, load 100%	0,85
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	391
Torque, Nm	354	Sound pressure Lp dB(A)	69
Starting torque ratio	2,4	Bearing DE	6314
Starting current ratio	8,3	Bearing NDE	6313
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	0,841
Note	IE4, Kopplingslåda med 2 x M16 + 1 x M16	2 x M63, 1 x M16	
	Färg svart		

