

SSWE280M-4 90KW 400/690V B5

Three-phase asynchronous motor in cast iron

Motor type SSWE280M-4 90KW 400/690V B5
Brand BUSCK
Item number 43042812

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	90	50	157,0	1485
690	90	50	90,3	1485
460	103,5	60	157,0	1782

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	96,1
Insulation class	F	Efficiency, load 75%	96
Cooling	IC411 (TEFC)	Efficiency, load 50%	95
Max. ambient temp.	40°C	Power fact, load 100%	0,86
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	623
Torque, Nm	579	Sound pressure Lp dB(A)	70
Starting torque ratio	2,2	Bearing DE	6317
Starting current ratio	7,8	Bearing NDE	6314
Winding protection	Thermistors	Balance grade	Normal
		Inertia kgm ²	1,77
Note	IE4, Kopplingslåda med 2 x M16 + 1 x M16 2xM63, 1xM16		
	Färg svart		

