

T4A132MA-6 4KW 400/690V B14


Three-phase asynchronous motor in aluminum

Motor type T4A132MA-6 4KW 400/690V B14
Brand BUSCK
Item number 43061333

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	4	50	8,72	975
690	4	50	5,01	975
460	4,6	60	8,72	1170

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	89,5
Insulation class	F	Efficiency, load 75%	89,8
Cooling	IC411 (TEFC)	Efficiency, load 50%	88,8
Max. ambient temp.	45°C	Power fact, load 100%	0,74
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	55
Torque, Nm	40,821	Sound pressure Lp dB(A)	68
Starting torque ratio	2,8	Bearing DE	6308-2Z/C3
Pull up torque ratio	3,4	Bearing NDE	6208-2Z/C3
Pull out torque ratio	1,8	Balance grade	Normal
Starting current ratio	8,0	Inertia kgm ²	0,053987
This motor has DNV type approval		Cable entries	2xM25, 1xM16

Note Termokontakt
IE4



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no