

T4A132MB-6 5,5KW 400/690V B3


Three-phase asynchronous motor in aluminum

Motor type T4A132MB-6 5,5KW 400/690V B3
Brand BUSCK
Item number 43061341

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	5,5	50	11,7	975
690	5,5	50	6,73	975
460	6,33	60	11,7	1170

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	90,5
Insulation class	F	Efficiency, load 75%	90,7
Cooling	IC411 (TEFC)	Efficiency, load 50%	89,7
Max. ambient temp.	45°C	Power fact, load 100%	0,75
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	68
Torque, Nm	56,128	Sound pressure Lp dB(A)	68
Starting torque ratio	3,3	Bearing DE	6308-2Z/C3
Pull up torque ratio	3,3	Bearing NDE	6208-2Z/C3
Pull out torque ratio	1,8	Balance grade	Normal
Starting current ratio	8,2	Inertia kgm ²	0,070723
This motor has DNV type approval		Cable entries	2xM25, 1xM16

Note Termokontakt
IE4



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no