

SSWE315S-6 75KW 400/690V B3

Three-phase asynchronous motor in cast iron

Motor type SSWE315S-6 75KW 400/690V B3
Brand BUSCK
Item number 43063151RL

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	75	50	136,7	980
690	75	50	78,6	980
460	86,25	60	136,7	1176

Duty	S1	Efficiency class	IE4
Enclosure	IP55	Efficiency, load 100%	95,4
Insulation class	F	Efficiency, load 75%	95,3
Cooling	IC411 (TEFC)	Efficiency, load 50%	94,3
Max. ambient temp.	40°C	Power fact, load 100%	0,83
Min. ambient temp.	-20°C		
Max. temp. rise	80 K	Painting	Standard
Max altitude, masl	1000	Color	RAL 9005
		Weight kg	803
Torque, Nm	730	Sound pressure Lp dB(A)	68
Starting torque ratio	2,0	Bearing DE	NU319
Pull out torque ratio	2,6	Bearing NDE	6319
Starting current ratio	7	Balance grade	Normal
Winding protection	Thermistors	Inertia kgm2	3,68
		Cable entries	2xM63, 1xM16

Note IE4, Kopplingslåda med FL21, 2x M63 + 1 x M16
Färg svart
Rullager på drivsidan

