

T4C315LB-2 200KW 500V B5

Single-phase asynchronous motor in aluminum

Motor type T4C315LB-2 200KW 500V B5
Brand BUSCK
Item number 43C23182T

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
500	200	50	269	2980
575	230	60	269	3576




Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 45°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 641
Starting torque ratio 1,8
Pull up torque ratio 0,8
Pull out torque ratio 2,2
Starting current ratio 8,5
This motor has DNV type approval

Note IE4

Efficiency class IE4
Efficiency, load 100% 96,5
Efficiency, load 75% 96,5
Efficiency, load 50% 96,0
Power fact, load 100% 0,89

Painting Standard
Color RAL 9005
Weight kg 1450
Sound pressure Lp dB(A) 92
Bearing DE 6317 C3
Bearing NDE 6317 C3
Balance grade Normal
Inertia kgm² 3,27
Cable entries 2xM63, 1xM16



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no