

ME90L-2 2,2KW 230/400V B35

Three-phase asynchronous motor in aluminum

Motor type ME90L-2 2,2KW 230/400V B35
Brand BUSCK
Item number 83020914TK

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
230	2,2	50	7,98	2860
400	2,2	50	4,59	2860
460	2,53	60	4,59	3432

Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 7,35
Starting torque ratio 4,1
Pull up torque ratio 3,3
Pull out torque ratio 4,1
Starting current ratio 7,9
Winding protection Thermocontacts

Efficiency class IE2
Efficiency, load 100% 83,3
Efficiency, load 75% 83,7
Efficiency, load 50% 81,9
Power fact, load 100% 0,83

Painting Standard
Color RAL 9005
Weight kg 15
Sound pressure Lp dB(A) 72
Bearing DE 6205-2Z/C3
Bearing NDE 6205-2Z/C3
Balance grade Normal
Inertia kgm² 0,00161
Cable entries 1xM20

Note IE2 Färg svart
Termokontakter

