

ME160L-2 18,5KW 400/690V B3

Three-phase asynchronous motor in aluminum

Motor type ME160L-2 18,5KW 400/690V B3
Brand BUSCK
Item number 83021621

Voltage V	Power kW	Frequency Hz	Current A	Speed rpm
400	18,5	50	32,3	2940
690	18,5	50	18,6	2940
460	21,28	60	32,3	3528


Duty S1
Enclosure IP55
Insulation class F
Cooling IC411 (TEFC)
Max. ambient temp. 40°C
Min. ambient temp. -20°C
Max. temp. rise 80 K
Max altitude, masl 1000

Torque, Nm 60
Starting torque ratio 3
Pull out torque ratio 3,5
Starting current ratio 9
Winding protection Thermistors

Note IE2 Färg svart

Efficiency class IE2
Efficiency, load 100% 90,9
Efficiency, load 75% 91,4
Efficiency, load 50% 90,8
Power fact, load 100% 0,91

Painting Standard
Color RAL 9005
Weight kg 104
Sound pressure Lp dB(A) 86
Bearing DE 6309-2Z/C3
Bearing NDE 6309-2Z/C3
Balance grade Normal
Inertia kgm² 0,066
Cable entries 2xM32 + 1xM16



BUSCK
www.busck.eu

Busck & Co AB
Gamla Riksvägen 14
428 32 Göteborg
Sweden
556027-1990
info@busck.se

Busck & Co ApS
Postboks 108
0900 København C
Denmark
info@busck.eu

Busck AS
Skibåsen 35C
4636 Kristiansand
Norway
info@busck.no