

# T712-4 0,37KW 208-220V 60HZ B14

## Single-phase asynchronous motor in aluminum

Motor type T712-4 0,37KW 208-220V 60HZ B14  
Brand BUSCK  
Item number 83040723ULk

| Voltage V | Power kW | Frequency Hz | Current A | Speed rpm |
|-----------|----------|--------------|-----------|-----------|
| 208       | 0,37     | 60           | 1,9       | 1720      |




Duty S1  
Enclosure IP55  
Insulation class F  
Cooling IC411 (TEFC)  
Max. ambient temp. 40°C  
Min. ambient temp. -20°C  
Max. temp. rise 80 K  
Max altitude, masl 1000

Torque, Nm 2,52  
Starting torque ratio 2,2  
Pull up torque ratio 1,9  
Pull out torque ratio 2,4  
Starting current ratio 4,5

Efficiency class IE2  
Efficiency, load 100% 77  
Efficiency, load 75% 76,50  
Efficiency, load 50% 73,20  
Power fact, load 100% 0,67

Painting Standard  
Color RAL 9005  
Weight kg 6  
Sound pressure Lp dB(A) 55  
Bearing DE 6204-2Z/C3  
Bearing NDE 6204-2Z/C3  
Balance grade Normal  
Inertia kgm<sup>2</sup> 0,000816  
Cable entries 1xM20

Note IE2 (T2A)  
CSA C US approved



**BUSCK**  
www.busck.eu

Busck & Co AB  
Gamla Riksvägen 14  
428 32 Göteborg  
Sweden  
556027-1990  
info@busck.se

Busck & Co ApS  
Postboks 108  
0900 København C  
Denmark  
info@busck.eu

Busck AS  
Skibåsen 35C  
4636 Kristiansand  
Norway  
info@busck.no